


# Low Profile T45-30E-1025

Low profiled sheets are designed for commercial and industrial buildings' facades and internal linings. Easy and fast to assemble, low profiled sheets are a perfect choice when both speed of construction and functionality are key.






# Properties



Model name	Low Profile T45-30E-1025
Effective width	1025 mm
Depth	40 mm
Width of valley	95 mm
Width of crown	30 mm
Minimum length	800 mm
Maximum length	12000 mm

## Perforation layout



10 % perforation, hole size  $d = 4$  mm, centres  $c = 12$  mm

15 % perforation, hole size  $d = 4$  mm, centres  $c = 10$  mm

30 % perforation, hole size  $d = 4$  mm, centres  $c = 7$  mm\*

40 % perforation, hole size  $d = 5$  mm, centres  $c = 7.5$  mm

\*) Standard solution in Ruukki® Acoustic Claddings

# Materials

Material	Material thickness (mm)	Weight (kg/m <sup>2</sup> )	Surface treatment
Steel	0.6	5.74	Galvanized
Steel	0.6	5.74	Polyester
Steel	0.6	5.74	GreenCoat Pural BT
Steel	0.7	6.70	Galvanized


# Coatings and colors

## GreenCoat Pural BT (Standard colours)


Gloss level: 20 GU (Satin) / 40 GU (Metallic)




RR20 Winter white



RR21 Pebble grey



RR23 Mountain grey



RR33 Nordic night black



RR40 Metallic silver



RR41 Metallic dark silver



RR42 Metallic gold



RR45 Metallic titanium



RR979 Metallic copper

---

## Extended colours

- GreenCoat Pural BT (steel)
- PVDF (aluminium)
- Powder paint (steel)
- Powder paint (aluminium)

# BIM objects



## Download BIM objects to your desktop

ProdLib brings Ruukki products as BIM models directly to your desktop in 3D form for design programs AutoCAD, Autodesk Revit, Archicad and Tekla Structures. Product libraries compile all necessary design models and detailed drawings in one place. Library updates are automatically notified, so as a user you can be sure that your product information is constantly up to date. ProdLib can also be used as a standalone desktop application.

[Go to BIM library](#)

## Download documents

### Declaration of performance

Design profile S18:



**Declaration of Performance 28/PP/VIM - Low profiles**  
PDF, 41.3 KB

Other design profiles:



**Declaration of Performance 25/PP/PAR - Cladding products**  
PDF, 43.7 KB

Cor-Ten design profiles:



**Ruukki Cor-Ten facades - Certification**  
PDF, 31.8 KB

### Order form



**Ruukki Design Profile order form 2.2.2**  
XLSM, 0.6 MB

## Maintenance instructions



### **Selection recommendation for color-coated products**

PDF, 1.6 MB



### **Ruukki Cor-Ten facades - maintenance instructions**

PDF, 70.3 KB



### **Ruukki powder coated facade claddings - Maintenance instructions**

PDF, 0.6 MB



### **Ruukki colour coated steel - Maintenance instructions**

PDF, 0.6 MB

## Accessory documents



### **Facade cladding accessories 02\_2025**

PDF, 4.1 MB

## References

## Visualization tool



### **Visualize your idea**

Get inspired on how our façade cladding products come live in a building façade. Find your own combination of surface structures, patterns, colors and materials.

[Go to visualization tool](#)