


Ruukki T130M & T153 - 3/15 web perforated + infill -Mineral wool

Load bearing T130M & T153 profile with web perforation is a **classical solution** to improve roof absorption properties moderately. Solution is integrated and efficient as normal mineral wool layers above the sheeting are utilized for sound absorption indoors.

Infill product in the profile groove improves sound absorption coefficient about 10 % and it improves also roof thermal insulation properties.


This solution is optionally available with following sustainable features:

- Steel facings made of recycled steel (SSAB Zero) for significantly lower CO₂ emissions and high circularity (Ruukki LowCarbon)



[SEND CONTACT REQUEST](#)

Structure



- 1. **T130M & T153** (web perforated 3 mm/15%)
- 2. Dust proofed acoustic infill, mineral wool, filling the groove, density 120...150 kg/m³
- 3. Absorption layer: Mineral wool 30 mm, density > 120 kg/m³
- 4. Vapor barrier, e.g. PE, t= 0,2 mm
- 5. Mineral wool 130...400 mm, density > 70 kg/m³
- 6. Upper layers and roof membrane according to project

Sound absorption values


Absorption coefficient and class for construction

Class D, α_w 0,45

f(Hz)	α_p 1/1
125	0,95
250	1,00

500	1,00
1000	0,60
2000	0,40
4000	0,35

Design tools



Ruukki Acoustic Estimator

Try our estimator for your next project. With our estimation tool you can calculate which product configuration provides you with optimal results.

[Go to estimation tool here](#)



Poimu software for dimensioning load-bearing sheets

Dimensioning software, Poimu, allows you to optimise product choice according to the Eurocode. Simply by defining some basic input data you can select a load-bearing sheet for their needs from Ruukki's selection. This quick optimisation tool covers 1-, 2-span and continuous structures and gives the exact solution as to what sheet should be used, as well as its length.

[Go to Poimu software](#)



Download BIM objects to your desktop

ProdLib brings Ruukki products as BIM models directly to your desktop in 3D form for design programs AutoCAD, Autodesk Revit, Archicad and Tekla Structures. Product libraries compile all necessary design models and detailed drawings in one place. Library updates are automatically notified, so as a user you can be sure that your product information is constantly up to date. ProdLib can also be used as a standalone desktop application.

[Go to BIM library](#)

Technical documents

Here you can find all technical documents related to Ruukki's sound environment solutions. Documents are organised by document type.

Product description



Ruukki sound environment solutions - Product description 09_2022

PDF, 1.5 MB

Design instruction



Ruukki sound environment solution - Design instructions 10_2022

PDF, 5.5 MB



Sound insulation values for sandwich panels and various structures 02_2023

PDF, 5.9 MB

Installation instruction



Load bearing profiled sheet - Installation instructions 10_2022

PDF, 1.1 MB

Detail drawings



Load bearing sheets absorption structures

PDF, 281.8 KB



Load bearing sheet absorption structures

DWG, 405.7 KB



Acoustic cladding structure drawing

DWG, 313.5 KB



Acoustic cladding structure drawing

PDF, 389.1 KB

Accessories



Facade cladding accessories 10_2022

PDF, 4.2 MB



Profiled sheets and purlins accessories 01_2024

PDF, 4.0 MB

Certificates and approvals

Here you can find all certificates and approvals related to Ruukki's sound environment solutions. Documents are organized by document type.

Declaration of performance



Declaration of Performance 12/LBS/VIM - Load bearing products

PDF, 494.1 KB



Ruukki Cor-Ten facades - Certification

PDF, 31.8 KB



Declaration of Performance 10/PP/ZYR - Low profiles

PDF, 56.5 KB



Declaration of Performance 28/PP/VIM - Low profiles

PDF, 42.7 KB



Declaration of Performance 8/PP/VIM - Low profiles

PDF, 43.2 KB



Declaration of Performance 25/PP/PAR - Cladding products

PDF, 43.7 KB

Environmental product declaration



EPD Facade claddings 03_2023

PDF, 3.5 MB



RTS-EPD_49-20_RC_Colour_coated_EN

PDF, 1.0 MB



RTS-EPD_48-20_RC_Hot_dip_galvanised_EN

PDF, 0.5 MB