

Sandwich panel SP2B E-PIR

Sandwich panel **SP2B E-PIR** is available in thicknesses 40 - 150 mm.

It is a perfect solution for most buildings and structures, combining **high quality** with **very good technical properties**.

The core of this sandwich panel is made of rigid, HCFC-free, self-extinguishing and sustainable polyisocyanurate foam (PIR). Its **excellent thermal insulation properties** enable the decrease of panel thickness which transfers directly to lower transportation and assembly costs, as well as **significant savings** of building's life cycle costs.

As an option, the panel can be equipped with the integrated gaskets in the joint that provide reliable airtightness of the panel. Only panels with gaskets can be part of the full Ruukki airtightness package including dedicated details and accessories.


[Read more on airtightness package.](#)

Applications:

- External walls
- Internal walls
- Ceilings

This product is optionally available with following sustainable features:

- Steel facings made of recycled steel (SSAB Zero) for significantly lower CO2 emissions and high circularity - available as Ruukki LowCarbon
- Ruukki Airtightness package for lower CO2 emissions during the use phase of the building



[SEND CONTACT REQUEST](#)

The information on our website is accurate to the best of our knowledge and understanding. Although every effort has been made to ensure accuracy, the company cannot accept any responsibility for any direct or indirect damages resulting from possible errors or incorrect application of the information of this publication. We reserve the right to make changes.

Properties

Model name	Sandwich panel SP2B E-PIR
Standard module width	1100 mm
Optional module width (B)	1000 (D = 80, 100, 110, 120, 150 mm)
Minimum length	2000 mm
Maximum Length	18500 mm
External facing thickness	0.5 mm
Internal facing thickness	0.4 mm
External Fire Exposure	NRO
Air Tightness	q50=0,01 m3/hm2 (pressure and suction) for thicknesses ≥ 100 mm *

Thickness D (mm)	40	60	80	100	110	120	150
Weight (kg/m ²)	10	10.8	11.5	12.3	12.6	13	14.2
U-value (W/m ² K)	0.56	0.36	0.27	0.22	0.20	0.18	0.14
Sound insulation Rw (dB)	24	24	24	24	24	24	24
Reaction to fire	B-s2, d0	B-s2, d0	B-s2, d0	B-s2, d0	B-s2, d0	B-s2, d0	B-s2, d0
GWP-total, A1-A3 (kg CO ₂ ◇/m ²)	26,3	27,8	29,4	31,1	31,8	32,6	35,0
GWP-total, A1-A3 (kg CO ₂ e/m ²) for Ruukki® LowCarbon	-	-	-	-	-	-	-

Wall fire resistance values & max span horizontal / vertical orientation (m):	40	60	80	100	110	120	150
EI 15	-	-	-	6.0/7.5	6.0/7.5	6.0/7.5	6.0/7.5
EI 20	-	-	-	- / 3.0	- / 3.0	- / 3.0	- / 3.0
EW 15	-	-	-	6.0/7.5	6.0/7.5	6.0/7.5	6.0/7.5

EW 20	-	-	-	- / 4.0	- / 4.0	- / 4.0	- / 4.0
-------	---	---	---	---------	---------	---------	---------

* The airtightness (q50) is applicable only for the panels equipped with EPDM gaskets.

Detailed information regarding the application of fire resistance ratings can be obtained from Ruukki Sales.

All properties are declared in accordance with EN 14509 and related standards.

Coatings and colors

Materials

Facing	Coating	Gloss level (GU)	Corrosivity category	UV resistance	Colours
External	GreenCoat Pural BT Satin	20	C4	Ruv4-5	RAL9010 (RR126)
External	GreenCoat Pural BT Metallic	40	C4	Ruv4	RAL9006 (RR40), RAL9007 (RR41)
External	Polyester	35	C3	Ruv2-3	RAL1015 (RR807), RAL1021, RAL2003, RAL3000 (RR770), RAL3009 (RR29), RAL3013 (RR774), RAL5003 (RR4F8), RAL5005 (RR4A8), RAL5012 (RR408), RAL6011 (RR526), RAL6018 (RR5G8), RAL7015 (RR23), RAL7016 (RR288), RAL7035 (RR2B1), RAL7040 (RR287), RAL9002 (RR1G6), RAL9003 (RR106), RAL9006 (RR946), RAL9007, RAL9010 (RR1G5), Golden Oak
Internal	Polyester	35	C3	-	RAL9002 (RR1G6), RAL9010 (RR1G5)
Internal	PVC laminate *		C4	-	White

Facing		Corrosivity category
External	Stainless steel*	C4
Internal	Stainless steel*	C4

*) optional material

UV resistance describes how well the coating is able to keep its original colour and gloss levels in accordance with EN10169. The higher the class, the better the resistance.

Corrosivity categories describe the outdoor climate conditions in accordance with EN12944. The higher the category, the more corrosive environment.


Primary colors




RAL9010 Pure white RR1G5




RAL9002 Grey white RR1G6




RAL7035 Light grey RR2B1




RAL9006 White aluminium RR946



RAL9007 Grey aluminium



RAL7015 Slate grey RR23




RAL7016 Anthracite grey RR288


Complementary colors



RAL9003 Signal white RR106



RAL1015 Light ivory RR807



RAL7040 Window grey RR287



RAL5005 Signal blue



RAL5003 Sapphire blue RR4F8




RAL 5012 Light blue RR408



RAL3000 Flame Red RR770



RAL3013 Tomato red RR774



RAL3009 Oxide red RR29



RAL6011 Reseda green RR526



RAL 6018 Yellow green RR5G8



RAL2003 Pastel orange



RAL1021 Colza yellow



Golden oak


Profile options




Ribbed R550



Ribbed R275



Linear L25




Linear L



Micro M



Flat F



Ribbed R28

Modular width	Facing	Profile options
1100mm	External	L, L25, M, R28, R275, R550, F
	Internal	L, L25, F
1000mm	External	L, L25, M, R28, F
	Internal	L, L25, F

Stainless steel available for panel thicknesses 60, 80, 100, 110, 120 mm. For stainless steel only L profiling is available.

Design tools



Traypan® software for designing sandwich panels

With TrayPan®, you can design metal faced sandwich panels made by Ruukki. A panel structure can be designed as a single- or multi-span construction. You can easily give, with a few parameters, both suction and pressure loads caused by the wind. The application also calculates the necessary fasteners.

[Go to Traypan®](#)



Download BIM objects to your desktop

ProdLib brings Ruukki products as BIM models directly to your desktop in 3D form for design programs AutoCAD, Autodesk Revit, Archicad and Tekla Structures. Product libraries compile all necessary design models and detailed drawings in one place. Library updates are automatically notified, so as a user you can be sure that your product information is constantly up to date. ProdLib can also be used as a standalone desktop application.

[Go to BIM library](#)

Technical documents

Here you can find all technical documents related to Ruukki's sandwich panels. Documents are organised by document type. Click to enter document library.

**Product
descriptions**



**Accessory
documents**



Load tables



**Installation
instructions**



**Maintenance
instructions**



**Sound
insulation
values**



**Detail
drawings**



Certificates and approvals

Here you can find all certificates and approvals related to Ruukki's sandwich panels. Documents are organised by document type. Click to enter document library.

**Declaration of
performance**



**Environmental
product
declaration**




**Intruder
resistance
certificate**



**M1 Emission
Classification**



Visualization tool



Get inspired with our Sandwich Panel visualization tool

With our interactive Visualization tool for Ruukki sandwich panels, you can easily explore and customize the perfect combination for your building project.

[Go to visualization tool](#)