



Design Panel DP V3

Design plokštė V3 tinka vertikaliam montavimui. Šios plokštės leidžia kurti užapvalintos geometrijos fasadus. Minimalus lenkimo spindulys 800 mm. Priklausomai nuo storio, plokštė gali būti su PIR ar mineralinės vatos šerdimi.



PATEIKTI UŽKLAUSĄ

Savybės



Lentelė 1 – galimi matmenys

Plokštės storis D (mm)	Maks. ilgis L (mm)	Min. spindulys R (mm)
80, 100, 110, 120, 140, 150	6000	800

Lentelė 2 – Design plokštės DP V3 galimi storiai ir šerdies tipai


Storis (mm)	Šerdies tipas	DP V3
60	PIR	-
80	PIR	SP2B, SP2D
100	PIR	SP2B, SP2D
110	PIR	SP2B
120	PIR	SP2D, SP2E
140	PIR	-
160	PIR	-

80	mineralinė vata	nSPB
100	mineralinė vata	nSPB, nSPD
110	mineralinė vata	nSPB
120	mineralinė vata	nSPB, nSPD
140	mineralinė vata	nSPB
150	mineralinė vata	nSPB, nSPD
160	mineralinė vata	-
170	mineralinė vata	-
180	mineralinė vata	-
200	mineralinė vata	-
210	mineralinė vata	-
230	wmineralinė vata	-


All properties are declared in accordance with EN 14509 and related standards.

Spalvos ir padengimai


Vertical corner panels Design Panels V3 can be manufactured with different coatings, profile options and colors. The availability of specific features is compliant with the options existing for corresponding standard panels. NOTE: L25 is not available on internal face.




RAL1015 RR807




RAL3013 RR774




RAL5005 Signal blue




RAL6011 RR526



RAL7015 RR23




RAL7016 RR288




RAL7035 RR2B1



RAL9002 Grey white



RAL9006 RR946



RAL9007 Grey aluminium



RAL9010 RR1G5