

Ruukki acoustic cladding 50 mm

All Ruukki design and low profiles with 30% continuous perforation and suitable background insulation layer of 50 mm removes flutter echoes between vertical parallel surfaces and improves absorption properties of both wall and ceiling surfaces.


This solution is optionally available with following sustainable features:

- Steel facings made of recycled steel (SSAB Zero) for significantly lower CO₂ emissions and high circularity (Ruukki LowCarbon)



[SEND CONTACT REQUEST](#)

Structure



- 1. Ruukki design profile or low profile with 30 % perforation
- 2. Hat profile 0,6 mm; h = 50 mm, w = 70 mm
- 3. Rockwool with glass fibre felt ~ 85 kg/m³, 50 mm, not in Ruukki delivery
- 4. Base structure: Ruukki sandwich panel (SPA150E) / all kind of base structure

Thickness	50
Impact resistance class (EN 13964:2014)	-

Sound absorption values

Practical sound absorption coefficient α_p and sound absorption class

Class A, α_w 1,00

f(Hz)	α_p
125	0,30
250	0,85
500	1,00
1000	0,95
2000	0,95
4000	0,95

Sound insulation values


Airborne sound insulation value improvement

(Values below are measured with Ruukki sandwich panel (SPA150E) base structure, similar improvement with all sandwich panels.)

f(Hz)	R(dB) 1/3	R(dB) 1/1	F	B
50	32,2			
63	28,2	19,4		
80	14,9			
100	21,1			
125	23,0	22,1		
160	22,3			
200	23,9			
250	27,9	26,6		


315	30,7			
400	34,2			
500	37,2	36,0		
630	37,5			
800	32,7			
1000	30,0	32,7		
1250	40,5			
1600	46,1			
2000	45,5	46,8		
2500	49,9			
3150	56,3		x	
4000	62,2	59,8	x	
5000	66,6		x	x

Note. Signs F and B indicate that the declared result is an underestimate in this frequency band. The true value is larger.



$$R_w(C;C_{tr}) = 35 \text{ } (-2;-5) \text{ dB}$$

Design tools



Ruukki Acoustic Estimator

Zistite, aký materiál je pre vás najlepší. Vyskúšajte našu kalkulačku pre váš ďalší projekt. Pridaním rozmerov budovy a vyplnením nastavení materiálu v nástroji Ruukki Acoustic Estimator môžete zistiť, ktorá konfigurácia produktu poskytuje optimálne výsledky pre váš projekt.

[Prejsť na kalkulačku](#)

Stiahnite si BIM objekty do vášho počítača

ProdLib prináša produkty Ruukki ako modely BIM v 3D pre návrhové programy AutoCad, Autodesk Revit, Archicad a Tekla priamo na plochu vášho počítača. Knižnice produktov sústreďujú všetky potrebné návrhové modely a detailné výkresy na jednom mieste. Aktualizácie knižnice sú automaticky oznámené, takže ako používateľ si môžete byť istý, že k dispozícii sú vždy najnovšie informácie o produkte. ProdLib je možné použiť aj ako samostatnú desktopovú aplikáciu.

[Prejsť do knižnice BIM](#)

Technical documents

Here you can find all technical documents related to Ruukki's sound environment solutions. Documents are organised by document type.

Product description



Ruukki sound environment solutions - Product description 10_2025

PDF, 1,6 MB

Design instruction

Installation instruction

Detail drawings

Accessories



Facade cladding accessories 02_2025 ENG

PDF, 4,1 MB



Profiled sheets and purlins accessories 01_2024

PDF, 4,0 MB

Certificates and approvals

Here you can find all certificates and approvals related to Ruukki's sound environment solutions. Documents are organized by document type.

Declaration of performance



Ruukki Cor-Ten facades - Certification

PDF, 31,8 KB



Declaration of Performance 28/PP/VIM - Low profiles

PDF, 41,3 KB



Declaration of Performance 8/PP/VIM - Low profiles

PDF, 43,6 KB

Environmental product declaration